



N° 870522056-2

1. NAME AND IDENTIFICATION CODE

PRODUCT: Compact High-Pressure Decorative Laminates (HPL) – Compact lam for indoor and outdoor application. Thickness between 6 y 20 mm.

2. MANUFACTURER NAME AND ADDRESS

Lamitech S.A.S.

Zona Industrial de Mamonal Km 13, Cartagena - Colombia

3. APPLICATION

Indoor application walls or ceilings subject to reaction to fire regulation, Classification B-s2, d0 (t<10 mm) and B-s1, d0 (t≥10 mm)
and outdoor application walls or ceilings subject to reaction to fire regulation, Classification: B-s2, d0.

4. PERFORMANCE EVALUATION AND VERIFYING SYSTEM.

System 1

5. NOTIFIED ORGANIZATION.

NAME: TECNALIA R&I CERTIFICACION, S.L.

ASSIGNMENT: Evaluation of the constancy of performance

EVALUATION SYSTEM: 1

DOCUMENT AND DATE OF ISSUE: Product performance certificate of completion
054607-2. November 24/2015

6. DECLARED PERFORMANCE

Característica esenciales	Prestaciones	Especificaciones Técnicas armonizadas
Reacción al fuego / reaction to fire / brandverhalten	Euroclase B-s2, d0 (t<10 mm) B-s1, d0 (t≥10 mm)	EN438 – 7: 2005
Resistencia al fuego/Fire Resistance / feuerwiderstand	NDP	
Permeabilidad al vapor de agua/wáter vapour resistance / Wasserdampfdurchlässigkeit	NDP	
Resistencia a las fijaciones / resistance to fixings / Verankerungsfestigkeit	6-8 mm: 2000 N 8-10 mm: 3000 N 10-20 mm: 4000 N	
Aislamiento acústico al ruido aéreo/ direct airborne sound insulation/direkte luftschalldämmung	NPD	
Resistencia de tracción en flexión/flexural stendgth / Biegefestigkeit	PASA / PASS / BESTANDEN	
Resistencia /Conductividad térmica	NDP	
Contenido en pentaclorofenol/pentachlorophenol content /Pentachlorophenol - Gehalt	NDP	
Emisión de formaldehído/reléase of formaldehyde/ formaldehydabgabe	E1	
Absorción acústica/sound absorotion/schallabsorption	NDP	
Resistencia al choque térmico/termal shock resistance /temperaturwechselbestandigkeit	PASA / PASS / BESTANDEN	
Densidad/density/dichte	1350 kg/m ³	
Resistencia a la Humedad/durability resistance to wet conditions / dauerhaftigkeit – bestandigkeit gegen feuchte	PASA / PASS / BESTANDEN.	
Resistencia al agua hirviendo/durability to immersion in boiling wáter /		

dauerhaftigkeit – beständigkeit gegenüber eintauchen in siedendes wasser	PASA / PASS / BESTANDEN	
--	-------------------------	--

7. PRODUCT CE LABELING AND DOCUMENTS: the product will use a small CE label just as well as dispatch documents

Declared performances in point 1 comply with those in point 6

This declaration of performance is issued under sole responsibility of the manufacturer identified in point 2

Signed for and on behalf of the manufacturer LAMITECH S.A.S

Ing. Jesus Ortega C.
Integrated management system engineer Lamitech S.A.S.

Cartagena – Colombia, Enero 11 / 2023

Lamitech